

Embedded Systems Design and Applications with the 68HC12 and HCS12

Errata Sheet, Last revised August 22, 2005

Contact steveb@uwyo.edu

Note: To determine printing number, find the ISBN number opposite page iii. Above the ISBN are the numbers 10 9 8... The last number in the series indicates the printing number.

1st Edition, 1st Printing

Location	Error	Submitted by
Pg. 87, 5 th line from bottom	Change "3.5" to "3.3"	M. Kheir
Pg. 98, line 28	Change code line to PORTA = ~PORTA; to toggle PORTA	P. Arkoudopoulos
Pg. 183, TCTL3 and 4 description	Change Figure "4.34" to "4.35"	M. Kheir
Pg. 208, line 12 of code	Add "}" to close if (mins ctr==60)	M.Kheir
Pg. 285, Fig 4.100, 4.100	All "+" symbols in both diagrams should be divide by symbols	S. Barrett, University of Wyoming
Pg. 353, Figure 5.22	One end of each 10K resistor should be connected to ground rather than Vcc. The software is using active high polling.	M. Kheir
Pg. 354, Figure 5.23	Remove "No" from beneath "Initialize LCD"	M. Kheir
Pg. 515, line 6	Change "\$9FFF" to "\$09FF"	Jean-Claude Lucot