Section 9 WYDOT Sample Exam



WMTC Concrete Training & Certification Seminar

Sample WYDOT Written Examination

1. The minimum sample size for consistency test is 1/4 cubic

2. Molding of cylinders and beams must begin within how many

minutes after collecting the composite sample

foot.

a)

b)

True

False

minated arter	concerning the composite campio.
a)	5 minutes
b)	10 minutes
c)	15 minutes
d)	30 minutes
e)	no time limits
	nt generates heat the fastest and is typically used
for high early	strength gain or for cold weather mixes?
a)	Type I
b)	Type I/II
c)	Type II
d)	Type III
e)	Type V
According to	WYDOT, beams and cylinders shall be cured for
•	ours at a temperature range of 60F to 80F.
a)	True
b)	False
	a) b) c) d) e) Which cemer for high early a) b) c) d) e) According to the first 48 hora)

5.	Many factors	s affect concrete durability including:
	a)	Strength
	b)	Entrained air content
	c)	W/CM ratio
	d)	Curing
	e)	All of the above
3.	The following	g can be added on-site to a batch of concrete:
	a)	Water
	b)	Slump enhancing admixture with engineer's
		approval
	c)	Air enhancing admixture with engineer's
		approval
	d)	All of the above
7.	Concrete ad	dmixtures can:
	a)	Adjust set time
	b)	Reduce water demand
	c)	Increase workability
	d)	Entrain Air
	e)	All of the above

cuft,	and whe	n the bucket if full of concrete weighs 43.0) lbs,
calcu	late the u	nit weight of the fresh concrete.	
	a)	144.2 lbs/cuft	
	b)	145.6 lbs/cuft	
	c)	158.2 lbs/cuft	
	d)	145.6 lbs/cy	
	e)	None of the above	
10. For	PCCP ar	nd structural concrete, the minimum air co	ntent
of f	resh conc	rete according to WYDOT is:	
	a)	4.5 %	
	b)	6.0 %	
	c)	7.5 %	
	d)	8.0 %	
	e)	8.5%	
11. Acc	ording to	QC/QA for PCCP, a sublot cannot exceed	what
frac	tion of a "	Paved Lot."	
	a)	1/2	
	b)	1/3	
	c)	2/5	
	d)	1/10	
	e)	1/16	0_1
			U_/I

8. According to QC/QA, the contractor is responsible for quality

9. If the tare weight of the container is 6.75 lbs, volume is 0.249

control of all materials and constructed structures.

True

False

a)

b)

	b)	False
13.	50F and 90F a)	
14.	,	all not be placed on frozen subbase or base.
	a)	True False
15.	exceed the rebe increased a)	

12. Increasing the w/cm ratio will improve the durability of

concrete, especially the freeze/thaw resistance?

True

a)

For the given aggregate properties, compute the following:

 $W_{DRY} = 6.78 \text{ lbs}$

 $W_{SSD} = 7.15 lbs$

 $W_{WFT} = 7.75 lbs$

16. How much water is absorbed by the aggregate?

- a) 7.15 lbs
- b) 0.37 lbs
- c) 0.60 lbs
- d) 0.97 lbs
- e) None of the above

17. Calculate the percent of free moisture>

- a) 8.85 %
- b) 8.39 %
- c) 14.31 %
- d) 13.57 %
- e) None of the above

18. If the fresh concrete temperature is 79F, what is the maximum placing time?

- a) 30 minutes
- b) 90 minutes
- c) 45 minutes
- d) 72 minutes
- e) None of the above

19.	is 564 lbs/cy, a) b) c) d)	
20.	If the w/cm ranet water available 32.5 lbs/cy, of for a 5 cy bar a) b) c) d)	atio = 0.45, cement content = 517 lbs/cy, and the ailable from the fine and coarse aggregate is compute the total amount of mix water required tch. 1163 lbs 1326 lbs
21.		t ft

22.	Calculate the rate of evaporation for the following
	condition: Air Temp. 80F, Relative Humidity 20%,
	Concrete Temp 80F, Wind Velocity 22 mph.
	a) 0.1 lb/sqft per hr
	b) 0.2 lb/sqft per hr

- c) 0.3 lb/sqft per hr
- d) 0.2 lb/sqyd per day
- e) None of the above

23.	When the evaporation rate exceeds	lb/sqft per
	hr, WYDOT requires the contractor to take	precautions to
	avoid plastic shrinkage cracking.	

- 0.02 a)
- b) 0.20
- c) 2.00
- d) No upper limit
- None of the above e)
- 24. It is acceptable to place winter curing blankets on the previously placed concrete just before going home for the day or within the next few days.
- True a)
- b) **False**